MITEL PROGRAMMABLE KEY MODULES IMPROVE CALL HANDLING WITH INTUITIVE PROGRAMMABLE KEY MODULES



Mitel[®] Programmable Key Modules (PKMs) extend the button capacity of the MiVoice 5324, 5330, 5330e, 5340, and 5340e IP Phones, as well as the MiVoice 8528 and 8568 Telephones.

Ideal for receptionists, departmental administrative assistants and people who require additional personal keys, PKMs can be easily programmed through the phone and can be used to monitor and manage multiple lines beyond the original capacity of the phone.

IMPROVE CAL HANDLING

Administrative assistants can use the 12- and 48-button Programmable Key Modules (PKMs) to monitor and manage multiple lines beyond the capacity of the MiVoice IP or digital phones. The 12-button PKM adds 12 keys, while the 48-button PKM adds 48 additional keys with one module or 96 keys with two 48-button PKM modules linked together. A Mitel PKM Interface Module added to the back of the phone allows the 12- and 48-button PKMs to easily connect, without the need for an additional local area network (LAN) port or digital line port. When used in either an enterprise or small business environment, the PKMs improve call handling for both employees and customers.

EASY TO PROGRAM

The PKMs, 12, 48 or 96 additional keys can be easily programmed as feature keys, speed call keys, extension keys, direct station select (DSS) keys or line appearance keys. Each key on the PKM has an associated indicator light, which gives the status of that extension or programmed feature. Personal keys can be easily programmed through the phones themselves or using the browser-based configuration tool.





PHYSICAL

DIMENSION (L X W X D)	WEIGHT	VOICE QoS
PKM 12: 6.75 in x 2.25 in (17 cm x 5.7 cm) PKM 48: Size: 7.25 in x 9.25 in (18.4 cm x 23.5 cm)	PKM 12: Weight: 0.6 lbs (0.3 kg) PKM 48: Weight: 2.1 lbs (0.9 kg)	IEEE 802.1 p/q

POWERING OPTIONS

POWER CONSUMPTION	MIVOICE 5324, 5330, 5330E, 5340, AND 5340E IP PHONES	MIVOICE 8528 AND 8568 TELEPHONES
PKM 12: 1.3 W PKM 48: 1.7 W	IEEE 802.3af Power over Ethernet (PoE) support from the phone's power source	Require an external 24 V DC power adapter to power the PKMs (purchased separately)

SYSTEM REQUIREMENTS

· MiVoice Business - Release 5.0 or later (formerly Mitel Communications Director (MCD))

• MiVoice Office – Release 5.0 or later (formerly Mitel 5000 Communications Platform)

· Mitel SX-200 IP Communications Platform (ICP) – Release 4.0 (UR5) or later

SUPPORTED PHONES

- · MiVoice 5324 IP Phone
- · MiVoice 5330 IP Phone*
- · MiVoice 5330e IP Phone
- · MiVoice 5340 IP Phone*
- · MiVoice 5340e IP Phone
- · MiVoice 8528 Telephone
- MiVoice 8568 Telephone

*SX-200 ICP does not support PKMs on the MiVoice 5330 and 5340 IP Phones.

MITEL | SIMPLY COMMUNICATING®

10.31.13

GLOBAL HEADQUARTERS	U.S.	EMEA	CALA	ASIA PACIFIC
Tel: +1(613) 592-2122	Tel: +1(480) 961-9000	Tel: +44(0)1291-430000	Tel: +1(613) 592-2122	Tel: +61(0) 2 9023 9500
Fax: +1(613) 592-4784	Fax: +1(480) 961-1370	Fax: +44(0)1291-430400	Fax: +1(613) 592-7825	Fax: +61(0) 2 9023 9501

FOR MORE INFORMATION ON OUR WORLDWIDE OFFICE LOCATIONS, VISIT OUR WEBSITE AT MITEL.COM/OFFICES

mitel.com



THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. The information furnished in this document, believed by Mitel to be accurate as of the date of its publication, is subject to change without notice. Mitel assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains.

M MITEL (design) is a registered trademark of Mitel Networks Corporation. All other products and services are the registered trademarks of their respective holders.

© Copyright 2013, Mitel Networks Corporation. All Rights Reserved.